

View Online at <https://aerobasegroup.com/nsn/5930-01-406-3873>

**Body Style:**

Bushing mount

**Bushing Length:**

0.469 inches

**Body Length:**

1.336 inches

**Body Width:**

0.734 inches

**Body Height:**

1.203 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.432 inches

**Actuator Height:**

0.921 inches

**Actuator Position-action Relationship:**

Center position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

Weapon systems-wasp class lhd; whidbey island class lsd

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive ac and 25.000 amperes resistive dc

**Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 screw

**Specification Data:**

96906-ms24612 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0