# NSN 5930-01-407-8788

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-407-8788

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.170 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.210 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.370 inches single actuator

#### **Overall Diameter:**

1.100 inches

#### Individual Section Quantity:

4

#### End Application:

F15s amt

#### Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section front

#### **Throw Quantity:**

12 single section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

12 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section front

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-01-407-8788

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level and 5.0 amperes inductive load dc at sea level

## Style Designator:

Tap, circular, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A052b0