NSN 5930-01-407-8900

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-407-8900

Thread Class:

2a single mounting facility

Overall Length:

2.220 inches

First Flat Length:

0.250 inches single actuator

Shaft Length:

0.370 inches single actuator

Overall Diameter:

1.150 inches

Individual Section Quantity:

1

End Application:

F155 amt

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

4 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

85.0 amperes resistive load ac at sea level and 2.5 amperes inductive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

NSN 5930-01-407-8900

Rotary Switch - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0