

View Online at <https://aerobasegroup.com/nsn/5930-01-408-6286>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.510 inches

Body Width:

0.320 inches

Body Height:

0.450 inches

Actuator Style:

Round

Actuator Diameter:

0.690 inches

Actuator Height:

0.240 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 250.0 ac

End Application:

F15s amt

Mounting Surface To Terminal End Distance:

0.610 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.467 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Special Features:

Mounting hardware includes hexnut and lockwasher

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0