

View Online at <https://aerobasegroup.com/nsn/5930-01-408-6286>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

0.510 inches

**Body Width:**

0.320 inches

**Body Height:**

0.450 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.690 inches

**Actuator Height:**

0.240 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 250.0 ac

**End Application:**

F15s amt

**Mounting Surface To Terminal End Distance:**

0.610 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.467 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes resistive ac

**Special Features:**

Mounting hardware includes hexnut and lockwasher

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0