## NSN 5930-01-411-8025



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-411-8025 **Thread Class:** 2a **Body Style:** Bushing/hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.080 inches **Bushing Length:** 0.562 inches **Body Length:** 0.850 inches **Body Width:** 0.375 inches **Body Height:** 0.680 inches **Case Material:** Metal **Switch Actuator Quantity: Actuator Style:** Round **Actuator Diameter:** 0.125 inches **Actuator Height:** 0.320 inches **Actuator Adapter Style:** Pushbutton **Adapter Bushing Length:** 0.560 inches **Maximum Voltage Rating In Volts:** 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** O ring Thready Qty Per Inch (tpi): 32

## Thread Size:

0.375 inches

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

## **NSN 5930-01-411-8025** Sensitive Switch - Page 2 of 2



Switch Release Force:
8.0 ounces
Switch Actuating Force:
36.0 ounces
Actuator Movement:
0.020 overtravel inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc
Thread Series Designator:
Unef
Terminal Type And Quantity:
1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0