NSN 5930-01-411-8025



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-411-8025 **Thread Class:** 2a **Body Style:** Bushing/hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.080 inches **Bushing Length:** 0.562 inches **Body Length:** 0.850 inches **Body Width:** 0.375 inches **Body Height:** 0.680 inches **Case Material:** Metal **Switch Actuator Quantity: Actuator Style:** Round **Actuator Diameter:** 0.125 inches **Actuator Height:** 0.320 inches **Actuator Adapter Style:** Pushbutton **Adapter Bushing Length:** 0.560 inches **Maximum Voltage Rating In Volts:** 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** O ring Thready Qty Per Inch (tpi): 32

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

NSN 5930-01-411-8025 Sensitive Switch - Page 2 of 2



| Switch Release Force: |
|---|
| 8.0 ounces |
| Switch Actuating Force: |
| 36.0 ounces |
| Actuator Movement: |
| 0.020 overtravel inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive dc |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 1 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |