

View Online at <https://aerobasegroup.com/nsn/5930-01-413-7927>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.310 inches single mounting facility

**Overall Length:**

2.810 inches

**First Flat Length:**

0.218 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.215 inches single actuator

**Shaft Length:**

0.430 inches single actuator

**Overall Diameter:**

1.030 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Coded and pile-up

**Mounting Method:**

Threaded bushing single mounting facility

**Pile-up Contact Form Arrangement:**

1a single switch single section in-line

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

100.0 milliamperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Decimal, 1 pole - 12 positions single section

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0