

View Online at <https://aerobasegroup.com/nsn/5930-01-413-7927>

Thread Class:

2a single mounting facility

Thread Length:

0.310 inches single mounting facility

Overall Length:

2.810 inches

First Flat Length:

0.218 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.215 inches single actuator

Shaft Length:

0.430 inches single actuator

Overall Diameter:

1.030 inches

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Coded and pile-up

Mounting Method:

Threaded bushing single mounting facility

Pile-up Contact Form Arrangement:

1a single switch single section in-line

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level

Contact Arrangement Truth Table:

Decimal, 1 pole - 12 positions single section

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0