

View Online at <https://aerobasegroup.com/nsn/5930-01-415-2467>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

2.090 inches

**Body Diameter:**

0.620 inches

**Bushing Length:**

0.440 inches

**Body Length:**

1.070 inches

**Actuator Style:**

Round, flush

**Actuator Diameter:**

0.880 inches

**Actuator Height:**

0.190 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.465 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac and 1.500 amperes inductive ac and 0.500 amperes lamp ac

**Special Features:**

Environmentally sealed; silver alloy contacts; dpdt; alternate action; 0.176 in. Maximum plunger travel; 1000 vrms dielectrical strength at sea level

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0