

View Online at <https://aerobasegroup.com/nsn/5930-01-415-2467>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.090 inches

Body Diameter:

0.620 inches

Bushing Length:

0.440 inches

Body Length:

1.070 inches

Actuator Style:

Round, flush

Actuator Diameter:

0.880 inches

Actuator Height:

0.190 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.465 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 1.500 amperes inductive ac and 0.500 amperes lamp ac

Special Features:

Environmentally sealed; silver alloy contacts; dpdt; alternate action; 0.176 in. Maximum plunger travel; 1000 vrms dielectrical strength at sea level

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0