

View Online at <https://aerobasegroup.com/nsn/5930-01-416-0615>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

0.615 inches

Body Diameter:

0.380 inches

Body Length:

0.445 inches

Overall Diameter:

0.437 inches

Actuator Style:

Round

Actuator Diameter:

0.190 inches

Actuator Height:

0.080 inches

Actuator Color:

Gray single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive ac and 4.000 amperes resistive dc

Test Data Document:

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

81349-mil-prf-8805/110 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.