

View Online at <https://aerobasegroup.com/nsn/5930-01-417-3767>

**Body Style:**

Hole mount

**Body Diameter:**

Between 0.990 inches and 0.995 inches

**Body Length:**

1.000 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.990 inches and 0.995 inches

**Actuator Style:**

Round, stepped

**Actuator Diameter:**

Between 0.998 inches and 1.030 inches

**Actuator Height:**

0.768 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained and left position momentary and right position momentary

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**End Application:**

Velocity pool reparable piece parts; helicopter, electronic countermeasures, eh-60a; helicopter, carrier based asw, sh-60f; engine, aircraft, j69-t-25 (t-37b); helicopter, search and rescue, hh-60h; aircraft, c-2a (reprocured); helicopter, uscg search and rescue, hh-60j

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 four throw, normally open, momentary action single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes inductive dc and 5.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Test Data Document:**

81349-mils9419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 tab, solder lug

**Specification Data:**

96906-ms27708 government standard

**Shelf Life:**

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0