

View Online at <https://aerobasegroup.com/nsn/5930-01-417-3767>

Body Style:

Hole mount

Body Diameter:

Between 0.990 inches and 0.995 inches

Body Length:

1.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.990 inches and 0.995 inches

Actuator Style:

Round, stepped

Actuator Diameter:

Between 0.998 inches and 1.030 inches

Actuator Height:

0.768 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained and left position momentary and right position momentary

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

Velocity pool reparable piece parts; helicopter, electronic countermeasures, eh-60a; helicopter, carrier based asw, sh-60f; engine, aircraft, j69-t-25 (t-37b); helicopter, search and rescue, hh-60h; aircraft, c-2a (reprocured); helicopter, uscg search and rescue, hh-60j

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 four throw, normally open, momentary action single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes inductive dc and 5.000 amperes inductive ac

Special Features:

Weapon system essential

Test Data Document:

81349-mils9419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab, solder lug

Specification Data:

96906-ms27708 government standard

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0