

View Online at <https://aerobasegroup.com/nsn/5930-01-421-1332>

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

5.013 inches

**Overall Diameter:**

1.083 inches

**Individual Section Quantity:**

10

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section periphery

**Throw Quantity:**

3 each section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section periphery

**Contact Load Current Rating:**

75.0 milliamperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Test Data Document:**

81349-mil-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-3786/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0