

View Online at <https://aerobasegroup.com/nsn/5930-01-422-8177>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Body Diameter:**

0.670 inches

**Bushing Length:**

0.469 inches

**Body Length:**

1.260 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

0.983 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Center position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac and 5.000 amperes inductive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 socket, integrated wire termination

**Specification Data:**

96906-ms21347 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0