

View Online at <https://aerobasegroup.com/nsn/5930-01-425-5050>

Thread Class:

2a single mounting facility

Thread Length:

0.155 inches single mounting facility

Overall Length:

1.915 inches

First Flat Length:

0.245 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.335 inches single actuator

Overall Diameter:

1.225 inches

Nonturn Device Radius:

0.380 inches at 6: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

3 each section

Switch Actuator Indexing Position Quantity:

2 all actuators

Shaft Type:

Round, flatted all actuators

Terminal Type:

Turret

Contact Load Current Rating:

140.0 milliamperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Un single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0