

View Online at <https://aerobasegroup.com/nsn/5930-01-425-5050>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.155 inches single mounting facility

**Overall Length:**

1.915 inches

**First Flat Length:**

0.245 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.335 inches single actuator

**Overall Diameter:**

1.225 inches

**Nonturn Device Radius:**

0.380 inches at 6: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

3 each section

**Switch Actuator Indexing Position Quantity:**

2 all actuators

**Shaft Type:**

Round, flatted all actuators

**Terminal Type:**

Turret

**Contact Load Current Rating:**

140.0 milliamperes resistive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Un single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0