

View Online at <https://aerobasegroup.com/nsn/5930-01-426-1170>

Thread Class:

2b

Body Style:

Bushing mount

Bushing Length:

0.170 inches

Body Height:

0.600 inches

Actuator Style:

Round

Actuator Diameter:

0.286 inches

Actuator Height:

0.440 inches

Actuator Position-action Relationship:

Up position momentary

Actuator Position-locking Relationship:

Down position locked out

Maximum Voltage Rating In Volts:

115.0 ac

End Application:

Weapon systems-arleigh burke class ddg; spruance class dd (963); wasp class lhd; ticonderoga class cg (47); an/sqq-89 surface ship asw combat system

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes resistive ac

Special Features:

Weapon systems essential

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNF

Terminal Type And Quantity:

6 printed circuit

Specification Data:

96906-ms21355 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0