

View Online at <https://aerobasegroup.com/nsn/5930-01-426-5311>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.469 inches

Body Length:

0.550 inches

Body Width:

0.572 inches

Body Height:

0.550 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Weapon systems-ticonderoga class cg (47); an/sqq-89 surface ship asw combat system; wasp class lhd; arleigh burke class ddg; spruance class dd (963)

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Weapon system essential

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 printed circuit

Specification Data:

96906-ms21357 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0