NSN 5930-01-433-5876



Push Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-01-433-5876 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Corrosion resistant and salt spray resistant **Bushing Length:** 1.060 inches **Body Length:** 1.090 inches **Body Width:** 1.770 inches **Actuator Style:** Round, flush **Actuator Diameter:** 1.188 inches **Actuator Height:** 1.060 inches **Maximum Voltage Rating In Volts:** 600.0 ac or 250.0 dc **End Application:** AIRC-ON-DIT-IONE **Inclosure Type:** Uninclosed **Mounting Method:** Panel **Features Provided:** Neutral terminal **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 1.200 amperes resistive ac and 0.550 amperes resistive dc **Special Features:** Next assembly 9454108 & 9454121; used on fdecu; ul listed (nema) 4, 4x, and 13; drainage holes; thermosetting cathodic epoxy coating **Terminal Type And Quantity:** 2 compression and 1 solderless lug Shelf Life: N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A053a0