## NSN 5930-01-436-4866

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-436-4866

| Body Style:   |
|---|
| Hole mounted  |
| Hazardous Locations/environmental Protection:                                     |
| Corrosion resistant and salt spray resistant and watertight                       |
| Unthreaded Mounting Hole Diameter:  |
| Between 0.255 inches and 0.260 inches   |
| Switch Actuator Quantity:   |
| 1   |
| Actuator Length:  |
| 3.000 inches  |
| Actuator Style:   |
| Roller arm  |
| Actuator Roller Diameter:   |
| 0.880 inches  |
| Actuator Roller Width:  |
| 0.280 inches  |
| Housing Height:   |
| 3.190 inches  |
| Housing Width:  |
| 3.250 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 2.810 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:  |
| 2.440 inches  |
| Maximum Voltage Rating In Volts:  |
| 600.0 ac  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Unthreaded hole   |
| Contact Load Current Rating At Maximum Rated Voltage:                             |
| 2.500 amperes resistive ac  |
| Precious Material And Location:   |
| Contacts silver   |
| Specification Data:   |
| 30003-1741as487 manufacturers source control                                      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## **NSN 5930-01-436-4866** Sensitive Switch - Page 2 of 2



Fiig:

A053a0