NSN 5930-01-436-4866

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-436-4866

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant and salt spray resistant and watertight
Unthreaded Mounting Hole Diameter:
Between 0.255 inches and 0.260 inches
Switch Actuator Quantity:
1
Actuator Length:
3.000 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.880 inches
Actuator Roller Width:
0.280 inches
Housing Height:
3.190 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.810 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.440 inches
Maximum Voltage Rating In Volts:
600.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Contact Load Current Rating At Maximum Rated Voltage:
2.500 amperes resistive ac
Precious Material And Location:
Contacts silver
Specification Data:
30003-1741as487 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-01-436-4866 Sensitive Switch - Page 2 of 2



Fiig:

A053a0