NSN 5930-01-440-4114

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-440-4114

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

1.416 inches

Overall Diameter:

0.750 inches

Individual Section Quantity:

1

End Application:

Radio terminal set, an/srq-4; spruance class dd (963); arleigh burke class ddg; oliver perry class ffg; ticonderoga class cg (47)

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Special Features:

Weapon system essential

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Specification Data:

81349-mil-s-3786/39 government specification

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-01-440-4114

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0