

View Online at <https://aerobasegroup.com/nsn/5930-01-444-6142>

Overall Length:

Between 1.465 inches and 1.510 inches

Overall Height:

0.550 inches

Body Diameter:

0.720 inches

Mounting Slot Width:

0.104 inches

Body Height:

0.360 inches

Distance Between Mounting Facility Centers:

Between 0.937 inches and 0.999 inches

End Application:

V6u824.6198e6 e/i fscm 03950

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -10.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

185.00 actuation point degrees fahrenheit and 182.00 deactuation point degrees fahrenheit and 188.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level first voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-prf-24236 spec.