NSN 5930-01-445-3632

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-445-3632 **Thread Class:** 2a single mounting facility **Thread Length:** 0.375 inches single mounting facility **Overall Length:** 1.937 inches **Overall Diameter:** 1.344 inches **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 4 single section rear **Mounting Method:** Threaded bushing w/panel seal single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Contact Load Current Rating:** 200.0 milliamperes resistive load highest ac voltage rating at sea level and 20.0 milliamperes inductive load highest ac voltage rating at sea level **Style Designator:** Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5930-01-445-3632 Rotary Switch - Page 2 of 2



Fiig:

A052b0