

View Online at <https://aerobasegroup.com/nsn/5930-01-448-2759>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

Between 0.570 inches and 0.580 inches

Body Width:

Between 0.530 inches and 0.540 inches

Body Height:

Between 0.725 inches and 0.735 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.423 inches and 0.433 inches

Actuator Height:

Between 1.155 inches and 1.160 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position no locking action and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

Between 0.735 inches and 0.745 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes lamp dc and 5.000 amperes resistive dc and 2.000 amperes inductive dc

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0