

View Online at <https://aerobasegroup.com/nsn/5930-01-448-2759>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.450 inches and 0.490 inches

**Body Length:**

Between 0.570 inches and 0.580 inches

**Body Width:**

Between 0.530 inches and 0.540 inches

**Body Height:**

Between 0.725 inches and 0.735 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.423 inches and 0.433 inches

**Actuator Height:**

Between 1.155 inches and 1.160 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

Between 0.735 inches and 0.745 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.468 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes lamp dc and 5.000 amperes resistive dc and 2.000 amperes inductive dc

**Test Data Document:**

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0