

View Online at <https://aerobasegroup.com/nsn/5930-01-450-3210>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**Overall Length:**

2.165 inches

**First Flat Length:**

0.230 inches all actuators and 0.270 inches all actuators

**Flat Height:**

0.219 inches 1st actuator

**Shaft Diameter:**

0.248 inches 1st actuator and 0.251 inches 1st actuator

**Shaft Length:**

0.750 inches 2nd actuator

**Overall Diameter:**

Between 0.672 inches and 0.702 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

9 2nd actuator

**Shaft Type:**

Round, flatted w/through hole 1st actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

30.0 milliamperes resistive load dc at sea level and 200.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0