

View Online at <https://aerobasegroup.com/nsn/5930-01-450-3211>

Thread Class:

2a single mounting facility

Thread Length:

0.292 inches single mounting facility and 0.332 inches single mounting facility

Overall Length:

2.165 inches

First Flat Length:

0.230 inches all actuators and 0.270 inches all actuators

Flat Height:

0.219 inches 1st actuator

Shaft Diameter:

0.248 inches 1st actuator and 0.251 inches 1st actuator

Shaft Length:

0.750 inches 2nd actuator

Overall Diameter:

Between 0.672 inches and 0.702 inches

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

9 2nd actuator

Shaft Type:

Round, flatted w/through hole 1st actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

30.0 milliamperes resistive load dc at sea level and 200.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0