

View Online at <https://aerobasegroup.com/nsn/5930-01-450-3635>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Width:**

0.910 inches

**Body Height:**

1.706 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.050 inches

**Actuator Position-locking Relationship:**

Center position locked in

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0