

View Online at <https://aerobasegroup.com/nsn/5930-01-453-2549>

Thread Class:

3a all pressure connection

Thread Direction:

Right-hand all pressure connection

Overall Length:

3.265 inches

Outside Diameter:

0.435 inches all connections

Body Diameter:

1.480 inches

Body Length:

0.960 inches

Overall Diameter:

1.595 inches

End Application:

Hh65 coast guard helicopter

Pressure Switch Type:

Differential

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.437 inches all pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, plug

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

2.70 actuation point pounds per square inch and 3.30 actuation point pounds per square inch and 1.50 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external all connections

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0