

View Online at <https://aerobasegroup.com/nsn/5930-01-453-5924>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.465 inches

**First Flat Length:**

0.350 inches single actuator

**Flat Height:**

0.100 inches single actuator

**Shaft Diameter:**

0.150 inches single actuator

**Shaft Length:**

0.400 inches single actuator

**Overall Diameter:**

0.360 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Slotted bushing at 12: 00 o'clock

**End Application:**

Hc-130 coast guard aircraft

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 each section rear

**Throw Quantity:**

10 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Momentary Position:**

Counterclockwise single actuator

**Rotor Through Connection Quantity:**

1 single section

**Cam Actuated Switch Contact Arrangement:**

1 pole, single throw, both positions maintained each switch each section rear

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

200.0 milliamperes inductive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0