

View Online at <https://aerobasegroup.com/nsn/5930-01-453-5924>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.465 inches

First Flat Length:

0.350 inches single actuator

Flat Height:

0.100 inches single actuator

Shaft Diameter:

0.150 inches single actuator

Shaft Length:

0.400 inches single actuator

Overall Diameter:

0.360 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

End Application:

Hc-130 coast guard aircraft

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section rear

Throw Quantity:

10 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Rotor Through Connection Quantity:

1 single section

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, both positions maintained each switch each section rear

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

200.0 milliamperes inductive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0