

View Online at <https://aerobasegroup.com/nsn/5930-01-454-5489>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

Between 0.658 inches and 0.718 inches

**Bushing Length:**

Between 0.595 inches and 0.655 inches

**Body Length:**

1.000 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.250 inches

**Actuator Free Position Height:**

Between 0.845 inches and 0.905 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

0.040 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0