

View Online at <https://aerobasegroup.com/nsn/5930-01-458-1159>

Thread Class:

2a all threaded stud

Thread Length:

0.500 inches all threaded stud

Overall Length:

2.750 inches

Overall Height:

7.406 inches

Overall Width:

2.875 inches

Body Height:

4.531 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.468 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.906 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Threaded stud

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded stud

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+10.00/+121.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point lock ring

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0