# NSN 5930-01-458-8946

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-458-8946

Th	read	C	ass:

2a single pressure connection

**Thread Direction:** 

Right-hand single pressure connection

**Overall Length:** 

70.0 millimeters

**Outside Diameter:** 

0.438 inches single connection

**Overall Height:** 

180.0 millimeters

**Overall Width:** 

53.0 millimeters

**Body Height:** 

80.0 millimeters

**Pressure Switch Type:** 

Differential

#### **Operating Tempurature Rating:**

Between -50.0 degrees celsius and 70.0 degrees celsius

**Mounting Method:** 

Bracket

### Thready Qty Per Inch (tpi):

20 single pressure connection

**Contact Action Stimulus:** 

Increase

**Thread Size:** 

0.438 inches single pressure connection

## **Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:** 

Connector, receptacle

#### **Contact Load Current Rating:**

16.0 amperes resistive load single voltage

#### **Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

#### **Contact Adjustment Range:**

+3.00/+30.00 actuation point bar

#### **Contact Adjustment Type:**

Internal actuation point screw and internal actuation point screw with scale

#### **Contact Stimulus Rating:**

3.50 differential point bar and 12.00 differential point bar

#### **Contact Voltage Rating In Volts:**

380.0 ac at sea level single voltage

# **NSN 5930-01-458-8946**Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded external single connection
Frequency In Hertz:
50.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0