

View Online at <https://aerobasegroup.com/nsn/5930-01-459-5450>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.610 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.990 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.312 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Retaining plate

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

13.0 ounces

Actuator Movement:

0.015 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac and 250.0 milliamperes resistive dc

Special Features:

Microswitch mounted on retaining plate using two no. 6 lockwashers and two pan head screws, no. 6 by 32 by 0.88 in; retaining plate has two mounting slots; switch actuator overtravel is 0.140 in. Min. And differential is 0.0004 in. ; dash 2 on part number indicates left side

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0