

View Online at <https://aerobasegroup.com/nsn/5930-01-460-1293>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.260 inches

**Overall Height:**

1.643 inches

**Overall Width:**

1.200 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.090 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

**Operating Temperature Range:**

-20.0/+75.0 degrees celsius

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel single actuator

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f single section

**Contact Arrangement Truth Table:**

Special single section

**Special Truth Table Identification:**

97525-special 1-2-4-8 single section

**Special Features:**

Notched terminals to mount to pc boards; double pole binary coded switch

**Color:**

White single indicator marking

**Precious Material And Location:**

Circuit disc surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0