

View Online at <https://aerobasegroup.com/nsn/5930-01-460-1293>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.260 inches

Overall Height:

1.643 inches

Overall Width:

1.200 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.090 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Temperature Range:

-20.0/+75.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f single section

Contact Arrangement Truth Table:

Special single section

Special Truth Table Identification:

97525-special 1-2-4-8 single section

Special Features:

Notched terminals to mount to pc boards; double pole binary coded switch

Color:

White single indicator marking

Precious Material And Location:

Circuit disc surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0