

View Online at <https://aerobasegroup.com/nsn/5930-01-463-2768>

**Overall Length:**

0.2715 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.251 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

2.655 inches single actuator

**Overall Diameter:**

1.188 inches

**Individual Section Quantity:**

4

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**End Application:**

High frequency radio repair

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

6 each section front

**Throw Quantity:**

5 each section front

**Mounting Method:**

Strut single mounting facility

**Contact Voltage Rating In Volts:**

6.0 dc at sea level

**Switch Actuator Momentary Position:**

Counterclockwise all actuators

**Rotor Through Connection Quantity:**

12 each section

**Switch Actuator Indexing Position Quantity:**

5 all actuators

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees all actuators

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

0.1 amperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Decimal, 2 pole - 5 positions each section

**Special Features:**

Spring clips silver alloy with gold flash; rotor blades coin silver alloy; marking plate included with all switches

**Precious Material And Location:**

Clips gold and clips and rotor blades silver

**Precious Material:**

Gold and silver

**Style Designator:**

Circular, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0