

View Online at <https://aerobasegroup.com/nsn/5930-01-463-3886>

**Body Style:**

Hole mounted

**Switch Actuator Quantity:**

1

**Actuator Style:**

Roller arm

**Housing Height:**

1.785 inches

**Housing Length:**

4.685 inches

**Housing Width:**

1.875 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.344 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.158 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 240.0 dc

**End Application:**

Bow thruster

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Actuator Movement:**

Between 18.0 pretravel degrees and 57.0 overtravel degrees and 10.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

6.000 amperes resistive ac and 0.150 amperes inductive dc and 0.400 amperes resistive dc

**Special Features:**

This p/n is the standard switch without modifications

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0