

View Online at <https://aerobasegroup.com/nsn/5930-01-463-5688>

Thread Class:

2b

Body Style:

Bushing mount

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

Between 0.910 inches and 0.930 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.400 inches and 0.440 inches

Actuator Height:

Between 1.030 inches and 1.070 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Actuator Position-locking Relationship:

Center position locked in and left position locked in and right position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Rsip ppl

Mounting Surface To Terminal End Distance:

1.180 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Nonturn feature

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0