

View Online at <https://aerobasegroup.com/nsn/5930-01-463-5688>

**Thread Class:**

2b

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.450 inches and 0.490 inches

**Body Length:**

1.270 inches

**Body Width:**

0.635 inches

**Body Height:**

Between 0.910 inches and 0.930 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.400 inches and 0.440 inches

**Actuator Height:**

Between 1.030 inches and 1.070 inches

**Actuator Position-action Relationship:**

Center position maintained and left position maintained and right position maintained

**Actuator Position-locking Relationship:**

Center position locked in and left position locked in and right position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Rsip ppl

**Mounting Surface To Terminal End Distance:**

1.180 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Nonturn feature

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0