NSN 5930-01-463-6024

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-463-6024

Overall Length: 4.000 inches **Overall Diameter: 2.813 inches Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **End Application:** Control panel **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 2 each section front **Throw Quantity:** 8 each section front **Mounting Method:** Bracket single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 600.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 4.0 amperes inductive load highest ac voltage rating at sea level **Precious Material And Location:**

Rotor and stationary contacts plated silver

Precious Material:

Silver

NSN 5930-01-463-6024

Rotary Switch - Page 2 of 2



Sty	16	u	=5	ıu	 aı	u	ч.	_

Circular, cam actuated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0