

View Online at <https://aerobasegroup.com/nsn/5930-01-463-7331>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Body Diameter:**

0.469 inches

**Bushing Length:**

0.282 inches

**Body Length:**

0.885 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round, flush

**Actuator Diameter:**

0.156 inches

**Actuator Height:**

0.136 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Radar system improvement program (rsip ppl)

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes inductive dc and 1.000 amperes inductive ac and 1.000 amperes resistive dc and 1.000 amperes resistive ac

**Special Features:**

Emi; hex nut ms25082-14 required; plunger seal

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0