NSN 5930-01-463-9069

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-463-9069

Body Style: Hole mounted Hazardous Locations/environmental Protection: Corrosion resistant and watertight Center To Center Distance Between Mounting Facilities Parallel To Length: 0.500 inches **Body Length:** 0.850 inches **Body Width:** 0.320 inches **Body Height:** 0.690 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches Actuator Length: 0.679 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** 0.756 inches Actuator Roller Diameter: 0.187 inches Actuator Roller Width: 0.187 inches Maximum Voltage Rating In Volts: 250.0 ac and 28.0 dc **Inclosure Type:** Hermetically sealed **Mounting Method:** Unthreaded hole Switch Release Force: 4.0 ounces Switch Actuating Force: 20.0 ounces **Actuator Movement:** Between 0.125 pretravel inches and 0.025 overtravel inches and 0.060 differential inches Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive ac **Special Features:** Single pole, normally open, double break **Terminal Type And Quantity:**

Wire lead

NSN 5930-01-463-9069

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

