

View Online at <https://aerobasegroup.com/nsn/5930-01-463-9069>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant and watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

0.850 inches

**Body Width:**

0.320 inches

**Body Height:**

0.690 inches

**Unthreaded Mounting Hole Diameter:**

0.112 inches

**Actuator Length:**

0.679 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.756 inches

**Actuator Roller Diameter:**

0.187 inches

**Actuator Roller Width:**

0.187 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

Between 0.125 pretravel inches and 0.025 overtravel inches and 0.060 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Special Features:**

Single pole, normally open, double break

**Terminal Type And Quantity:**

Wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0