

View Online at <https://aerobasegroup.com/nsn/5930-01-464-1112>

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.160 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.094 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

0.500 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**End Application:**

2350-01-436-0005 armored reconnaissance airborne assault vehicle

**Switch Contact Basic Design:**

Coded

**Pole Quantity:**

1 single section front

**Throw Quantity:**

16 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Detent Rotational Torque Range:**

+3.000/+18.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load highest dc voltage rating at sea level and 30.0 milliamperes inductive load highest dc voltage rating at sea level

**Contact Arrangement Truth Table:**

Bcd with complement, 1 pole - 16 positions single section

**Precious Material And Location:**

Contacts gold

**Precious Material:**

Gold

**Style Designator:**

Snap or line

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0