## NSN 5930-01-464-1112

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-464-1112

Thread Length:

0.250 inches single mounting facility

**Overall Length:** 

1.160 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

1

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

**End Application:** 

2350-01-436-0005 armored reconnaissance airborne assault vehicle

**Switch Contact Basic Design:** 

Coded

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

16 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

16 single actuator

**Shaft Type:** 

Round, flatted single actuator

Terminal Type:

Tab, solder lug

**Detent Rotational Torque Range:** 

+3.000/+18.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

125.0 milliamperes resistive load highest dc voltage rating at sea level and 30.0 milliamperes inductive load highest dc voltage rating at sea . . .

level

## NSN 5930-01-464-1112

Rotary Switch - Page 2 of 2

Fiig: A052b0



Contact Arrangement Truth Table:
Bcd with complement, 1 pole - 16 positions single section
Precious Material And Location:
Contacts gold
Precious Material:
Gold
Style Designator:
Snap or line
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No